



Mixing Solutions
As Unique As Your Needs
All Stainless Steel Sanitary Mixer Lines

SaniQuip® SGA Series

Tank Sizes from 1,000 to 20,000 liters



Sizes: 1/2 – 5 HP
Speeds: 100- 1000 RPM
Constant Torque, Servo Motor
Integral Planetary Gearbox
Shaft Diameter: 3/4" standard

Minimum footprint with integral tri-clamp mounting and stainless steel, light-weight servo motor and integral planetary gearbox

- All-stainless steel construction with smooth surfaces in an open pedestal design for superior wash-down capability
- Stainless steel brushless servo motor designed to handle IP67 and withstand 1500 psi washdown conditions
- Nema 4x, washdown duty servo drive with Smart Keypad and display provides continuous speed control and digital tachometer. Integrated output connections for direct data acquisition
- Stainless steel high precision, planetary gearbox with precision helical gearing for smooth and quiet operation
- Lubrication by synthetic Nyogel 72D grease for operation over the whole service life and sealed to IP65 standard for protection and maintenance-free performance
- Complete range of welded sanitary impellers, including hydrofoils, axial and radial turbines, and specialty designs
- In-tank wetted parts mechanically polished and EP from 35 Ra micro-inch to 5 Ra micro-inch finish
- Full range of shaft seals to meet application requirements

GUARANTEE

ProQuip, Inc. accepts full responsibility for furnishing suitable equipment which shall be fit for the purpose which it is required, and for its successful operation under the conditions for which it was specified

ProQuip, Inc.
Designers and Manufacturers of Agitation Equipment
850 East Highland Road • Macedonia, Ohio 44056-2190 USA
330-468-1850 • (fax) 330-467-3724
www.proquipinc.com • sales@proquipinc.com